

IMAGE PROCESSING DEVICE, PROGRAM PRODUCT AND METHOD

[0001] This application is based on Japanese Patent Application No. 2000-267304 filed on September 4, 2000, the contents of which are hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0002] The present invention relates to an image processing device, its program product and method. In particular, the invention relates particularly to an image processing device, its program product and method for synthesizing foreground image data consisting of character or graphic images with background image data.

2. Description of the Related Art

[0003] The presentation materials that are printed on overhead projector sheets often contain foreground image data containing character images, etc., placed in front of background image data.

[0004] However, there are cases where the boundaries of the foreground image data and the background image data become unidentifiable depending on the colors of the background image data that exist in the areas surrounding the foreground image data such as character images, etc. and consequently, the

colors of the background image data.

[0008] Therefore, it has been a problem that, when character images obtained by reading an original document on which characters are color-coded depending on the function of each character, such as a part of title, subtitle, and keyword, are synthesized with the background image data, color-adjusted character images after synthesization lose the color-coding information completely.

SUMMARY OF THE INVENTION

[0009] It is an object of the present invention to provide an improved image processing device, program product and method for solving various problems mentioned above.

[0010] It is a further object of the present invention to provide an image processing device, program product and method for securely identifying character images, etc., embedded in background image data without damaging color-coding information such as a title expressed in a uniform color on the foreground image data, in synthesizing foreground image data such as character images and background image data.

[0011] According to an aspect of the invention, it is an image processing device comprising: a first color detection means for detecting colors of a first image data by each processing unit; a second color detection means for detecting

colors of a second image data that serves as the first image data's background by each processing unit; and a color adjusting means for specifying a uniform adjusting color that makes the first image data recognizable against all colors of the second image data that serves as the first image data's background, concerning the first image data that have approximately equal colors.

[0012] According to another aspect of the invention, it is a program product for image processing that causes a computer to execute a process comprising the steps of: detecting colors of a first image data by each processing unit; detecting colors of a second image data that serves as the first image data's background by each processing unit; and specifying a uniform adjusting color that makes the first image data recognizable against all colors of the second image data that serves as the first image data's background, concerning the first image data that have approximately equal colors.

[0013] According to still another aspect of the invention, it is an image processing method comprising the steps of: detecting colors of a first image data by each processing unit; detecting colors of a second image data that serves as the first image data's background by each processing unit; and specifying a uniform adjusting color that makes the first image data recognizable against all colors of the second image

data that serves as the first image data's background, concerning the first image data that have approximately equal colors.

[0014] The objects, features, and characteristics of this invention other than those set forth above will become apparent from the description given herein below with reference to preferred embodiments illustrated in the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] Fig. 1 is a block diagram showing the general constitution of an image processing device according to an embodiment of the invention;

[0016] Fig. 2 is a flow chart showing the image processing of an image processing unit;

[0017] Fig. 3 is a flow chart showing the procedure of a synthesizing process;

[0018] Fig. 4 is an example of background image data;

[0019] Fig. 5 is an example of foreground image data;

[0020] Fig. 6 is a diagram describing how background colors are detected;

[0021] Fig. 7 is a diagram showing a correlation table;
and

[0022] Fig. 8 is an example of synthesizing image data.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0023] The embodiments of this invention will be described below with reference to the accompanying drawings.

[0024] Fig. 1 is a block diagram showing the general constitution of an image processing device according to an embodiment of the invention.

[0025] The image processing device has an image processing unit 10, an operating unit 20, a controller 30, an image input unit 40, and an image output unit 50.

[0026] The image processing unit 10 has a character recognition unit 11, an area separation unit 12, a bitmap processing unit 13, a vector conversion unit 14, a binarization unit 15, a synthesizing unit 16, a format conversion unit 17, and a memory 18, and is capable of applying a specified process to inputted foreground image data and synthesizing the foreground image data and the background image data.

[0027] Although it is not shown in the drawing, the operating unit 20 has a touch screen display and input keys and is used by the user for entering instruction information. The instruction information includes specifically the scanning start instruction for starting scanning of the document by the image input unit 40 and instructions for manual setup items.

[0028] The manual setup items include a setup for readout mode, a setup for post-processing, a setup for image synthesizing mode, and a setup for output format.

[0029] The readout mode includes the color mode for processing a document image as a color image and the monochromatic mode for processing a document image as a monochromatic image at the image input unit 40.

[0030] The setup for post-processing is a mode for selecting various post-processes to be applied to the areas that are separated by the area separation unit 12 and the character recognition unit 11 of the image processing unit 10, i.e., character areas, graphics areas, and photographic areas. The post-processes include character coding at the character recognition unit 11, bitmap processing at the bit map processing unit 13, vector conversion process at the vector conversion unit 14, and binarization process at the binarization unit 15.

[0031] The image synthesizing mode includes an "image synthesizing-no mode," in which the inputted image data are not synthesized at the image processing unit 10, an "image synthesizing-yes mode," in which the inputted image data are synthesized, in other words, recognized as foreground image data, and a "background input mode," in which the inputted image data are recognized as background image data.

the specified readout mode (color/monochromatic mode). The image data obtained by reading the document is transmitted to the image processing unit 10 via the interface 33.

[0036] The image output unit 50 has a first output unit 51 and a second output unit 52, and receives the image data transmitted from the image processing unit 10 via the interface 34. The first output unit 51 consists of an image forming device such as a color printer, and prints the image data on a recording medium such as a sheet of paper. The second output unit 52 consists of, for example, a computer equipped with a monitor, and the transmitted image data are displayed, stored or data processed.

[0037] Next, the operation of the image processing unit 10 will be described using the flow charts shown in Fig. 2 and Fig. 3.

[0038] First, at the step S11, character recognition processing will be performed for the image data inputted into the image processing unit 10.

[0039] If the background input mode is not set up here, the character recognition unit 11 extracts character areas where the character images exist from the inputted image data. The image data, from which the character areas have been removed, are inputted into the area separation unit 12.

[0040] The character recognition unit 11 recognizes

character codes from character images and converts them into character code data. The character recognition unit 11 detects character information such as position information, character counts and color information from character images. The position information includes the x-y coordinates, width information, and length (height) dimensions of the character images. The character recognition unit 11 outputs the character code data to the synthesizing unit 16 together with the character information containing the position information and the color information. If the binarization process is set up as the post-process by the user, the character area will be inputted into the binarization unit 15.

[0041] If the background input mode is set up here, the character recognition unit 11 transmits all the areas of the inputted image data to the area separation unit 12 identifying them as non-character areas.

[0042] At the step S12, the area separation process will be conducted to the image data, from which character images have been removed.

[0043] If the background input mode is not set up here, the area separation unit 12 separates the image data, from which character images have been removed, into graphic areas and photographic areas. Photographic images in the photographic areas will be added with position information

and transmitted to the bitmap processing unit 13, while graphic images in the graphic image areas will be added with position information and will be transmitted to the vector conversion unit 14.

[0044] On the other hand, if the background input mode is set up here, the area separation unit 12 identifies all the areas of the inputted image data as photographic areas and transmits photographic images in the photographic areas to the bitmap processing unit 13.

[0045] At the step S13, the bitmap processing unit 13 applies edge compensation and smoothing to the inputted photographic images in the photographic areas. After that, the data in the photographic area are inputted into the synthesizing unit 16 with the position information.

[0046] At the step S14, the vector conversion unit 14 vector-converts the inputted graphic images in the graphic areas to generate vector data. The vector conversion unit 14 detects attributive information including color information such as the color of the enclosed areas surrounded by the vector data, line widths, line types, line colors and endpoint shapes. The vector data are inputted into the synthesizing unit 16 together with the attributive information. The vector conversion means converting graphics consisting of mesh points into vector data such as

SECRET

[0052] On the other hand, at the step S22 it is judged whether the image synthesizing-yes mode is set up. In case it is the image synthesizing-yes mode (S22: Yes), the process of the step S23 is executed, while, in case it is the image synthesizing-no mode (S22: No), the process of the step S28 is executed.

– 13 –

background color is an average color of the colors of pixels in said circumscribing rectangle. The foreground image data are made up of character code data from the character recognition unit 11, vector data from the vector conversion unit 14, and binarized character image data from the binarization unit 15.

[0054] At the step S24, the synthesizing unit 16 enters the colors of the foreground image data, i.e., the foreground colors, and the background colors, into the correlation table shown in Fig. 7. This correlation table is stored in the memory 18.

[0055] The foreground colors are expressed, for example, by the RGB color system as (R_n, G_n, B_n) ($n = 1, 2, \dots$) and are stored into the foreground color column of the correlation table. The background colors are expressed, for example, by the RGB color system as $(R_{Bnm}, G_{Bnm}, B_{Bnm})$ ($n, m = 1, 2, \dots$), which are correlated to the foreground color of the corresponding position and are stored into the background color column of the correlation table.

[0056] Let the two foreground colors that are compared be expressed in the RGB color system as (R_i, G_i, B_i) and (R_j, G_j, B_j) . If the K value for those colors obtained from the following formula (1) is lower than a specified threshold value;

expressed by the coordinate value of the specified color system. More specifically, the average background color value can be calculated according to the following formula (2) as expressed, for example, in the RGB color system as (RAn, GAn, BAn):

$$\begin{aligned} R A n &= \sum_{l=1}^{l_{\max}} R B n l / l_{\max} \\ G A n &= \sum_{l=1}^{l_{\max}} G B n l / l_{\max} \\ B A n &= \sum_{l=1}^{l_{\max}} B B n l / l_{\max} \end{aligned} \quad (2)$$

where l_{\max} is the number of background colors correlated to the foreground color group.

[0059] At the step S26, the synthesizing unit 16 calculates the color of the foreground image data after the adjustment, i.e., the adjusting color, based on the color of the foreground color group and the average background color calculated in correspondence to the color of the foreground color group. In other words, the synthesizing unit 16 calculates an adjusting color that makes the boundary between the foreground image data and the background image data recognizable for all colors of the background image data.

[0060] The foreground colors and the average background colors of the correlation table are now color converted from

processing unit 13, the vector conversion unit 14, and the binarization unit 15. If the image synthesizing-yes mode is set up as the image synthesizing mode, the foreground image data and the background image data, i.e., its background, are synthesized. Both image data will be synthesized according to a predetermined internal format.

[0066] At the step S29, the format conversion unit 17 converts the image data synthesized according to the predetermined internal format into the output format specified by the user.

[0067] At the step S30, the format conversion unit 17 transmits the synthesized image data converted to the output format to the interface 34 connected to the image output unit 50.

[0068] Fig. 8 is a diagram showing an example of a synthesized image data produced by synthesizing the background image data shown in Fig. 4 and the foreground image data shown in Fig. 5.

[0069] The background image data here consists of a green leaf section 61 and a brown background section 62 (see Fig. 4). The foreground image data consists of a black character section 63, a red symbol section 64, and a deep green character section 65 (see Fig. 5). In the synthesized image data where both image data are synthesized, the black character section

63 of the foreground image data is color-adjusted to a white character section 73, and the deep green character section 65 is color-adjusted to red character section 75.

[0070] Therefore, each section of the foreground image data becomes recognizable against both the green leaf section 61 and the brown background section 62 of the background image data, making them more legible. Moreover, although the character sections 63 and 65 of the foreground image data are both overlapping with both of different color sections 61 and 62 of the background image data, they are not adjusted to easily identifiable colors on the background image data, and the character sections, which appeared as approximately same colors on the foreground image data, are color-adjusted into a uniform color. Thus, the designer's original color-coded information, e.g., the information for the title, subtitle and keyword, will be maintained in the foreground image data.

[0071] As can be seen from the above, the specific colors in the foreground image data having approximately same colors are adjusted to a uniform color, which makes the boundaries between the foreground image data and the background image data recognizable to all the colors of the background image data that serves as the background. Therefore, color-coding information such as the title expressed in a uniform color

09942173-083001
100280-2124650

on the foreground image data will not be lost from the synthesized image data obtained by synthesizing the foreground image data such as character images and its background, i.e., the background image data. Moreover, character images, etc., are easily legible against the background image data.

[0072] The invention is not limited to the above-mentioned embodiment, but rather can be changed in various ways with the scope of the claims of the patent.

[0073] For example, although it was described about a color copying system that functions as an image processing device equipped with the image input unit 40 consisting of a color scanner, etc., and the image output unit 50 having the first output unit 51 consisting of a color printer, etc., as well as the second output unit 52 consisting of a computer having a monitor, etc., the invention is not limited to it. For example, the invention can be applied to a digital color copying machine that has an image input unit and an image output unit built into the machine.

[0074] The invention also can be applied to a computer that functions as an image processing device. In this case, the image data can not only be prepared by the computer but also can be received from other information equipment such as a scanner or can be downloaded via a network.

[0075] Furthermore, it often happens with presentation materials that different foreground image data are drawn over the same background image data so that multiple sheets can be prepared quickly. In such a case, it is possible to transmit the background image data to the printer only once while transmitting as many foreground images as needed for synthesizing both images at the printer's controller.

[0076] Various means to constitute the image processing device and the image processing method according to this invention can be realized by a dedicated hardware circuit or a programmed computer. In realizing the invention by means of a programmed computer, the program for operating the computer can be provided by computer readable recording medium (e.g., flexible disk or CD-ROM). In this case, the program recorded on computer readable recording medium is normally transferred to the hard disk and stored. This program can be provided as independent application software or can be built into the software of the computer as a function of the computer. The program product in this invention includes the program itself as well as the computer readable recording medium on which the program is stored.